



January 2018



**ARLON**

**SLX™ CAST WRAP**  
with **FLITE Technology™**



Wrapped in SLX™ Cast Wrap and Series 3270 by Auto Artisan Group

## UNIQUE FEATURES:

- ▶ **Fast Wraps with One Installer**  
FLITE Technology™ allows graphics to float over the substrate until firm pressure is applied making it easy to install graphics with a single installer.
- ▶ **Superior Repositionability**  
Effortless repositionability across all print systems and high ambient temperatures. Snap up multiple times to ensure the correct graphic placement.
- ▶ **Effortless Liner Release**  
Prevents the graphic from stretching, maintaining its proportionate integrity.
- ▶ **Vibrant and Reliable Print Quality**  
Competitively superior and consistent print quality across all print systems. After the material is heated and stretched, the image quality is not compromised.
- ▶ **Stays Down in Deep Channels**  
No primer required to conform and bond in deep channels.
- ▶ **Clean Removability**  
Highly conformable around rivets, complex curves and deep channels. Will remove cleanly with heat.

*"With Arlon's new SLX™ Cast Wrap film, all of the features that we as installers require have been captured. From outstanding print quality, to an easy liner release, this film makes installation as easy as it's ever been!"*

**Michael Palladino**



Images courtesy of Michael Palladino | Auto Artisan Group

## SLX™ Cast Wrap + FLITE™ TECHNOLOGY

*It's Not Just Air Egress, It's Better!*

SLX™ Cast Wrap is a premium gloss white repositionable cast film with FLITE Technology™. Designed for the single installer, this film allows for a fast wrap and superior repositionability for full and partial, vehicle and fleet applications. FLITE Technology is a lite contact system allowing graphics to float over a substrate until firm pressure is applied. It guarantees the fastest installation while ensuring long-term bond, conforming effortlessly around rivets, complex curves and deep channels. SLX Cast Wrap offers a vibrant and reliable print quality which is present across Eco-Solvent, Solvent, Latex and UV print systems. Arlon strongly recommends the use of Series 3270 Overlaminates when using SLX Cast Wrap for optimum performance of the film.

## LEARN MORE:



Wrapping with SLX™ Cast Wrap  
[go.arlon.com/wrapping-with-slx-cast-wrap](http://go.arlon.com/wrapping-with-slx-cast-wrap)



What is FLITE Technology™ and How Does it Make Wrapping Easier?  
[go.arlon.com/what-is-FLITE](http://go.arlon.com/what-is-FLITE)

## INSTALLER TIPS:

- LITE CONTACT IS PART OF THE DESIGN**  
The adhesive will initially feel lite to the touch, but will build a long-term bond.
- USE THE RECOMMENDED OVERLAMINATE**  
Use SLX™ Cast Wrap with Series 3270 Overlaminates for optimal results.
- APPLY FIRM PRESSURE**  
Always apply firm squeegee pressure and overlap your squeegee strokes.
- ALWAYS POST-HEAT**  
Arlon recommends post-heating edges, seams and stretched areas.



	SLX™ Cast Wrap	Series 3270 Overlaminates
<b>Finish:</b>	Gloss	Gloss, Matte, Satin
<b>Film Life (Unprinted):</b>	7 Years	7 Years
<b>Adhesive:</b>	Clean Removing, Repositionable (Light Gray)	Permanent (Clear)
<b>Release Liner:</b>	Lay-Flat Polycoated with Low Profile FLITE Technology™	Clay Coated
<b>Compatible Ink:</b>	Eco-Solvent Solvent UV Latex	N/A