



ARLON

DPF 510GTR / MTR

DPF 510 delivers a consistent, vibrant print quality at an unbeatable value for your short-term applications. The two sided, lay-flat polycoated liner ensures that the vinyl will not curl under heavy heat from printers, is resistant to high humidity and makes your graphic easier to handle and install. DPF 510 has consistent ink receptivity across most print systems. The low tack removable solvent-based adhesive allows for easy removal of up to one year and can be used with dry or wet applications. Combine DPF 510 with Series 3510 overlamine for an easier installation and abrasion resistance.

Unique Features:

- ▶ Exceptional, Vibrant Print
- ▶ Consistent Performance with High Heat Printers
- ▶ High-Quality Clean Removing Adhesive

Applications:

- ▶ Short-Term Interior or Exterior Signage
- ▶ Windows
- ▶ Decals
- ▶ Interior Floor Graphics

Performance & Physical Data

Finish:	Gloss / Matte
Durability (Unprinted):	3 Years
Roll Widths*:	54" (1,37 m), 60" (1,52 m)
Roll Lengths:	50 Yards (45,72 m)
Adhesive:	Low Tack Removable (Tinted)
Release Liner:	Lay-Flat Polycoated
Ink Compatibility:	Eco-Solvent Solvent Latex
Compatible Overlamine:	Series 3510

*Sizes can be custom ordered



Certified for
HP Latex Inks

USA

- a** 200 Boysenberry Lane, Placentia, CA 92870
- p** 800 232 7161 / +1 714 985 6300
- f** +1 714 985 6305

EUROPE

- a** Dr. Lelykade 22B, 2583CM Den Haag, The Netherlands
- p** +31 70 354 4311
- f** +31 70 355 7721

CHINA

- a** No. 1989 Xinchang Road, Weifang, Shandong, 262400
- p** +86 0536 6226568

arlon.com

November 2020