



ARLON

DPF 6000RP White

DPF 6000RP White is a gloss white cast film with tinted, high tack, permanent pressure-sensitive adhesive. Designed for large format graphics and train applications, DPF 6000RP White is made of premium quality cast facestock with a special lay-flat liner. The special adhesive system is designed to provide excellent opacity, as well as easy installation. The film provides superior conformability around rivets, curves, contours and channels. DPF 6000RP White is rated for outdoor durability up to 7 years (unprinted). Printed durability is dependent on the ink system used.

Unique Features:

- ▶ Conformable to Deep Channels
- ▶ All-Purpose Applications
- ▶ Smooth, Paint-Like Finish

Applications:

- ▶ Fleet, Vehicle Graphics and Train Applications
- ▶ Window Graphics
- ▶ Wall Graphics (Interior, Exterior)
- ▶ Multipurpose Commercial
- ▶ Certified for Europe Rail External Application in Combination with Series 3350



Performance & Physical Data

Finish:	Gloss
Durability (Unprinted):	7 Years
Roll Widths:	1.37 m, 1.52 m
Roll Lengths:	45.72 m
Adhesive:	Clean Removing, Repositionable (Light Gray)
Release Liner:	Lay-Flat Polycoated
Ink Compatibility :	Eco-Solvent Solvent UV Latex
Compatible Overlaminate:	Series 3200 Series 3210 Series 3220 Series 3270 Series 3310 Series 3350

Test Method	Result	Acceptability Cat Ib
Flame Spread:	Class 1 (nil spread)	Class 1
Smoke Emission:	A ₀ (ON) = 5.82 A ₀ (OFF) = 6.22	A ₀ (ON) < 7.0 A ₀ (OFF) < 10.5
Toxic Fume Emission:	R = 0.054	R < 2.7

BS 6853 1999 Annex D8.4 & BS 476 Part 7

USA: a 200 Boysenberry Lane, Placentia, CA 92870, USA
 EUROPE: a North Sea Building, Gevers Deynootweg 93, 4th Floor, 2586BK Den Haag, The Netherlands

p 800 232 7161 / 714 985 6300 f 800 329 2756
 p +31 0 70 354 4311 f +31 0 70 355 7721

arlون.com
 January 2019