



**ARLON**

# INTERIOR FLOOR OVERLAMINATES

Advertising at all angles is now possible with select Arlon overlaminates!

Series 3420 Matte and Series 3510 Matte are now an approved overlaminate under the AS 4586:2013 standard for slip resistance as an interior floor graphic material\*. When paired with either DPF 4600GLX/MLX, DPF 8200 High Tack, or DPF 510 GT/MT/GTR/MTR, this media and overlaminate combination can now produce more applications than you imagined.

## Unique Features:

- Classified under AS 4586:2013 Slip Resistance Classification of New Pedestrian Surface Materials. Appendix A (Wet Pendulum Test): Class P3, Appendix B (Dry Floor Friction Test): Class D1.

## Recommended Surfaces:

- ▶ Smooth Floors
- ▶ Low-Profile Carpet \*

Floor Graphic Details	
<b>Classification:</b>	AS 4586:2013
<b>Compatible Media:</b>	DPF 4600GLX / MLX DPF 8000™ Ultra Tack DPF 8200 High Tack DPF 510GT/MT DPF 510GTR/MTR
<b>Recommended Interior Surfaces:</b>	Waxed vinyl flooring Sealed concrete Marble Ceramic tile Sealed wood Terrazzo Low-pile commercial-grade carpet *



Certified for  
HP Latex Inks

\* For interior floor graphics on carpet, Arlon recommends DPF 8200 High Tack only

## USA

- 📍 200 Boysenberry Lane, Placentia, CA 92870
- 📞 800 232 7161 / +1 714 985 6300
- 📠 +1 714 985 6305

## EUROPE

- 📍 Dr. Lelykade 22B, 2583CM Den Haag, The Netherlands
- 📞 +31 70 354 4311
- 📠 +31 70 355 7721

## CHINA

- 📍 No. 1989 Xinchang Road, Weifang, Shandong, 262400
- 📞 +86 0536 6226568

[arlon.com](http://arlon.com)

June 2020